

TM-8102C 50W VHF (138-174 MHz)

TM-8402C 40W UHF (400-470 MHz)

The TM-8000C Series mobiles provide affordability and durability for your in-vehicle or dispatch applications. With crisp, continuous and high quality communications, you can have real time contact with drivers to ensure that your business is running efficiently. In addition, Maxon's mobile radios provide a wide range of voice and data features and the ability to create a portable repeater (and even crossband UHF/VHF) when you connect two repeaters with the TM-8000C repeater cable (XRC-31). Base station cabinet & installation services are also available for the TM-8000C series mobile.



- 512 Channels, Up to 32 Groups (Dynamic)
- Alpha Numeric Display (10 Characters)
- 12.5/25 kHz Channel Spacing
- User Selectable Squelch Control
- CTCSS/DCS
- DTMF ANI
- 2-Tone Decode
- Normal and Priority Scan Options
- User Adjustable Power, 40W (UHF) 50W (VHF)
- Remote Stun and Revive
- Four Programmable Function Buttons
- DE-15 Data Connector
- PA Function, External Speaker Jack
- POCSAG (option)



SPECIFICATIONS

GENERAL

TM-8102C	138-174 MHz
TM-8402C	400-470 MHz
Channel Spacing	12.5/25 KHz (Outside U.S.)
Dimensions (H/W/D)	1.75 x 6.5 x 6.75" (45x165x171.5 mm)
Weight	39.96 oz. (1.12 kg.)
Operating Voltage	13.8 V DC
PLL Channel Step	2.5/6.25 kHz
Frequency Stability	± 1.5 PPM (1.1 Kg to 140°F)
Current Drain	50 W Tx-10A, 25 W Tx-6.5A Rx @ Max Audio 800 mA Standby 13.8V. 70mA
Operating Temperature	-22° to 140° F (-30° to 60° C)
External Audio Jack	3.5mm 4 Watt/4 Ω

TRANSMITTER

Output Power	VHF 50 Watt, UHF 40 Watt
Spurious and Harmonic	70dB
FM Hum and Noise	40dB (12.5 kHz), 45dB (25 kHz)
Output Impedance	50 ohms
Audio Distortion	Less than 5% at rated output
Audio Response	+1, -3dB from 6dB per octave pre-emphasis and characteristic 300 ~ 3000 Hz

RECEIVER

Sensitivity	.25uV 12dB SINAD
Squelch Sensitivity	.22uV 10dB SINAD
Selectivity	65dB (12.5 kHz), 70dB (25 kHz)
Spurious and Harmonic	75dB
FM Hum and Noise	40dB (12.5 kHz), 45dB (25 kHz)
IF Frequencies	21.4 MHz and 455 kHz
Input Impedance	50 ohms
Audio Output Power	4 Watt
Audio Distortion	3% max w/ 1 kHz modulation
Audio Response	+1, -3dB from 6dB per octave pre-emphasis and characteristic 300 ~ 3000 Hz

PACKAGE INCLUDES:

Radio, heavy duty microphone, mounting hardware, and 12V fused power cable.

Specifications are subject to change without notice.

ACCESSORIES



ACCESSORY OPTIONS

- Heavy Duty Microphone
- Extra-Long 37" mic cord option
- 10 Amp Power Supply 110V/220V AC
- Programming Software and Cable (USB)
- Base Station Cabinet & Installation
- Desktop Base Station Microphone
- External Speaker
- XRC-31 Repeater Cable
- 12' or 20' Coax Mag Mount Base
- VHF or UHF Wave Antenna

Data Port Pin Out



DE-15 Female

Approvals	FCC	Industry Canada
TM-8102C	099TM-8102	9680A-TM8102
TM-8402C	099TM-8402A	9680A-TM8402A



Manufactured to ISO-9001:2000 quality standard.

NOTE: Some features indicated by specifications listed are prohibited by FCC rule and are not available on models sold in the U.S. or its territories.

maxon®
Maxon America, Inc.

11535 W. 83rd Terrace Lenexa, KS 66214

Tel: (800) 456-2071 - Tel: (913) 859-9515

Fax: (913) 859-9550

Web: www.maxonamerica.com

E-mail: maxon@maxonamerica.com